

BLUESIL THREAD SEALANT

Specially designed for Threaded pipes, fittings, valves etc.



Supreme has been a pioneer in introducing many innovative and cost effective plastic piping products. Supreme is also recognized as trend setters of plastic piping products. Our objective is to meet the growing needs of the customers in water, waste management and infrastructure sector through specially developed high performance piping range. The Supreme comprehensive and exclusive range of plastic pipe systems are designed and manufactured to meet the highest standards set across the world. Supreme has no doubt, brought about a revolution in the Indian plastic pipe industry.

After successfully introducing solvent cement, primer, and rubber lubricant, we are very happy to introduce one more useful and value added product called "thread sealant" under the brand name 'BLUESIL'. Looking at its quality and versatile features this path breaking product will be well accepted in the market.

Unique Features

- Non-Hardening, Lubricating, Anti-Seize Formulation
- Safe, Non-Toxic, Lead & Silicone Free
- Non-Corrosive, Non-Conductive
- Convenient Packing
- Specially designed for Supreme Threaded Fittings and Valves
- Can be used for all types of threaded joints like plastic to plastic, plastic to metal and metal to metal etc.
- Positive Seal
- Longer life





Formulated, Designed & Tested for all types of threaded joints

While many thread sealants and pipe joint compounds claim to be suitable for use with plastics, several have been found to produce stress cracking due to chemical incompatibility. Improper application of TFE tape sealants can result in overstressed threaded connections and potential joint failures. Research has proven Bluesil thread sealant to be the superior choice for reliable joint make-up of all Supreme thermoplastic piping products.

General Instructions

Store and apply between 20° F (-7° C) and 140° F (60° C): remains brushable to -50° F (-45° C). Stir before using.

- 1. Threads should be properly formed or cut with a good die and free of oils, dirt, moisture etc.
- 2. Apply Supreme Bluesil freely to male threads with brush applicator. Brush well into threads to ensure a leak-free joint.
- 3. Assemble joint in usual manner. Take care not to over tighten. System may be placed into service immediately.

Keep container closed when not in use. Stir before reuse. Do not reuse empty containers.

Caution: Do not take internally. Do not bum-fumes may be harmful. Wash hands and exposed areas after handling.

R	•			-			cific									
	a	₹	c	•	n	Δ	CI	н	п	c	a	tı	n	m	16	•
_	u	71	•	_	М	•	•	ш		•	ч		v	ш	-	

Color : Light Blue

: 100, 250, 500 and 1000 g. **Packing**

: Brushable paste, grit free Consistency

Shelf Life : 2 years **First Aid**

: Flush 15 minutes with clean water. Eyes

Skin : Wash with soap and water.

: Only if conscious, give large amounts Ingestion of water and induce vomiting. Obtain

medical attention.

The Supreme Industries Ltd. (Plastic Piping Division)

1161/1162, Solitair Corporate Park, Building No. 11,167, Guru Hargovindji Marg, Chakala, Andheri Ghatkopar Link Road, Andheri (East) Mumbai - 400 093. India. Tel: 91-22-6771 0000, 4043 0000 Fax: 6771 0099 / 4043 0099. Works: • Unit No.3, Gat No.47-48, at post

Gadegaon, Tal. Jamner Dist., Jalgaon. • D-101/102, MIDC, Jalgaon - 425 003 Export Division :91-22 -67710126/ 4043 0126 Fax : 67710130

• E-mail : pvc-pipes@supreme.co.in • Website : www.supreme.co.in

